


29.

The diagram on the right shows the forces acting on the plank. Since the roller is frictionless the force it exerts is normal to the plank and makes the angle θ with the vertical. Its magnitude is designated F . W is the force of gravity; this force acts at the center of the plank, a distance $L/2$ from the point where the plank touches the floor. N is the normal force of the floor and f is the force of friction. The distance from the foot of the plank to the wall is denoted by d . This quantity is not given directly but it can be computed using $d = h/\tan \theta$. The equations of equilibrium are:



$$\begin{array}{ll} \text{horizontal force components} & F \sin \theta - f = 0 \\ \text{vertical force components} & F \cos \theta - W + N = 0 \\ \text{torques} & Nd - fh - W \left(d - \frac{L}{2} \cos \theta \right) = 0 . \end{array}$$

The point of contact between the plank and the roller was used as the origin for writing the torque equation.

When $\theta = 70^\circ$ the plank just begins to slip and $f = \mu_s N$, where μ_s is the coefficient of static friction. We want to use the equations of equilibrium to compute N and f for $\theta = 70^\circ$, then use $\mu_s = f/N$ to compute the coefficient of friction.

The second equation gives $F = (W - N)/\cos \theta$ and this is substituted into the first to obtain $f = (W - N) \sin \theta / \cos \theta = (W - N) \tan \theta$. This is substituted into the third equation and the result is solved for N :

$$N = \frac{d - (L/2) \cos \theta + h \tan \theta}{d + h \tan \theta} W .$$

Now replace d with $h/\tan \theta$ and multiply both numerator and denominator by $\tan \theta$. The result is

$$N = \frac{h(1 + \tan^2 \theta) - (L/2) \sin \theta}{h(1 + \tan^2 \theta)} W .$$

We use the trigonometric identity $1 + \tan^2 \theta = 1/\cos^2 \theta$ and multiply both numerator and denominator by $\cos^2 \theta$ to obtain

$$N = W \left(1 - \frac{L}{2h} \cos^2 \theta \sin \theta \right) .$$

Now we use this expression for N in $f = (W - N) \tan \theta$ to find the friction:

$$f = \frac{WL}{2h} \sin^2 \theta \cos \theta .$$

We substitute these expressions for f and N into $\mu_s = f/N$ and obtain

$$\mu_s = \frac{L \sin^2 \theta \cos \theta}{2h - L \sin \theta \cos^2 \theta} .$$

Evaluating this expression for $\theta = 70^\circ$, we obtain

$$\mu_s = \frac{(6.1 \text{ m}) \sin^2 70^\circ \cos 70^\circ}{2(3.05 \text{ m}) - (6.1 \text{ m}) \sin 70^\circ \cos^2 70^\circ} = 0.34 .$$